

VERTICAL AUTOCLAVE AUT12-110ADC



VERTICAL AUTOCLAVE AUT12-110ADC

Laboratory Vertical Autoclave is designed to accommodate a wide range of applications. The user can choose to add the features needed according to intended use. Features are designed specifically for lab based sterilizations used in pharmaceuticals, microbiology labs, research laboratories, food and chemical industries. Very reliable and convenient method of sterilization.

Used in Food industry, Chemical industry, Research, Laboratory, Pharmaceutical.

Also known as Vertical Pressure Sterilizer, Vertical Pressure Autoclave, Vertical Sterilizer, Laboratory Vertical Autoclave,.

AUT12-110ADC VERTICAL AUTOCLAVE

- Microcomputer control system
- Stainless steel chamber
- Six sterilization modes
- Resin coated insulation of Chamber cover and bench to avoid hand burns
- User friendly control panel
- Waste sterilization mode and drying function
- Rounded corners avoid collisions and injuries
- Automatic sterilization according to preset time
- Temperature and pressure calibration interface
- Convenience of frequent water feeding
- Automatic monitoring of the discharge conditions of cold air
- Automatic opening of the vent valve to discharge steam on completion of sterilization procedure
- Fully automatic internal discharge control embedded with a steam trapping bottle
- Safety function: "Eight-column evenly distributed" interlocking device, electric double inner locks, dry scorch protection, overpressure protection, safety valve, over temperature protection, overcurrent and short circuit protection, leakage protection, cooling lock, anti-scald chamber cover and bench, automatic troubleshooting



SPECIFICATIONS

| Model | AUT12-110ADC |
|------------------------------|---|
| Capacity | 110 L |
| Function | Fully automatic, Automatic water feeding, Fast cooling fan, Drying function |
| Sterilization Temperature | 105-138°C |
| Sterilization Time | 1-300 min |
| Warming Temperature | 45—60°C |
| Warming Time | 1—9999 min |
| Melting Temperature | 60-100 |
| Melting Time | 1-300 min |
| Steam Exhausting Temperature | 73—104°C |
| Humidity Range | 10%-85% RH |
| Working Pressure | 0-0.6 MPa |
| Maximum Working Pressure | 0.27 MPa |
| Timer Range | 0 minute-6 days |
| Chamber Dimension | 400×895 mm |
| Overall Dimension (LxWxH) | 660x644x1180 mm |

| | |
|--------------|-------------|
| Weight | 125/170 kg |
| Power | 4600 W |
| Power Supply | 220 V, 60Hz |

ACCESSORIES

| Accessory Code | Name | Description |
|----------------|-------------------------|-------------|
| LS54437 | Stainless steel baskets | |
| LS54449 | Drainage hose | |
| LS54461 | Exhaust bottle | |

OPTIONAL ACCESSORIES

| Accessory Code | Name | Description |
|----------------|------------------------|-------------|
| LS54473 | Printer | |
| LS54485 | Printing set | |
| LS54497 | Load thermometer | |
| LS54509 | Cooling fan | |
| LS54521 | Temperature controller | |
| LS54533 | Temperature sensor | |
| LS54545 | Pressure Sensor | |
| LS54557 | Heater | |
| LS54569 | Sealing ring | |

| Accessory Code | Name | Description |
|----------------|----------------------|-------------|
| LS54581 | Pressure gauge | |
| LS54593 | Stainless steel pail | |
| LS54605 | Relay | |
| LS54617 | Main board | |
| LS54629 | Display board | |
| LS54641 | Jiggle switch | |
| LS54653 | Handle | |
| LS54665 | Pressure switch | |
| LS54677 | Solenoid Valve | |



Biozef

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: info@biozef.com | Website: biozef.com