

HORIZONTAL AUTOCLAVE AUT22-0280



HORIZONTAL AUTOCLAVE AUT22-0280

Laboratory horizontal autoclaves are useful in bulk sterilization applications of equipment and materials in various industries and research institutions. Also for disposing biological waste, reducing the risk of contamination and sterile the waste before discarding. We provide a variety of horizontal autoclave according to applications, features and customers requirements.

Used in Bulk sterilization, Microbiology Lab, Research Institutions, Laboratory, Pharmaceutical, Food industry, Chemical industry.

Also known as Laboratory Sterilizer, Horizontal Pressure Sterilizer, Laboratory Horizontal Autoclave,.

AUT22-0280 HORIZONTAL AUTOCLAVE

Drying function

Automatic sterilization process

Safety valve for over pressure protection

Over-temperature, over-pressure protection device

304 stainless steel material chamber

Automatically in case of low water level.

4 Water level sensor. The power will be cut-off

Double door optional

Interlock function



Product Image Coming Soon

SPECIFICATIONS

Model	AUT22-0280
Capacity	280 L
Chamber Size	Φ600x1000 mm
Working Pressure	0.22 Mpa
Working Temp.	134 °C
Temperature Range	105-134°C
Sterilization Time	0-60 min
Drying Time	0-60 min
Temp. Display Accuracy	≤±2°C
Consumption	12 KW
Power Supply	380 V, 50 Hz
External Size (W*D*H)	1400x770x1780 mm
Package Size (W*D*H)	1680x920x2100 mm
Gross Weight	465 kg



Biozef

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: info@biozef.com | Website: biozef.com