



HORIZONTAL AUTOCLAVE AUT22-0400

Laboratory horizontal autoclaves are useful in bulk sterilization applications of equipment and materials in various industries and research institutions. Also for disposing biological waste, reducing the risk of contamination and sterile the waste before discarding. We provide a variety of horizontal autoclave according to applications, features and customers requirements.

Used in Bulk sterilization, Microbiology Lab, Research Institutions, Laboratory, Pharmaceutical, Food industry, Chemical industry.

Also known as Laboratory Sterilizer, Horizontal Pressure Sterilizer, Laboratory Horizontal Autoclave,.

AUT22-0400 HORIZONTAL AUTOCLAVE

Drying function
Automatic sterilization process
Safety valve for over pressure protection
Over-temperature, over-pressure protection device
304 stainless steel material chamber
Automatically in case of low water level.
4 Water level sensor. The power will be cut-off
Double door optional
Interlock function



Product Image Coming Soon

SPECIFICATIONS

Model	AUT22-0400
Capacity	400 L
Chamber Size	Ф700x1100 mm
Working Pressure	0.22 Mpa
Working Temp.	134 °C
Temperature Range	105-134°C
Sterilization Time	0-60 min
Drying Time	0-60 min
Temp. Display Accuracy	≤±2°C
Consumption	18 KW
Power Supply	380 V, 50 Hz
External Size (W*D*H)	1430x880x1830 mm
Package Size (W*D*H)	1600x1050x2100 mm
Gross Weight	530 kg



Biozef

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA Email: info@biozef.com | Website: biozef.com