

HORIZONTAL AUTOCLAVE AUT22-150



HORIZONTAL AUTOCLAVE AUT22-150

Laboratory horizontal autoclaves are useful in bulk sterilization applications of equipment and materials in various industries and research institutions. Also for disposing biological waste, reducing the risk of contamination and sterile the waste before discarding. We provide a variety of horizontal autoclave according to applications, features and customers requirements.

Used in Bulk sterilization, Microbiology Lab, Research Institutions, Laboratory, Pharmaceutical, Food industry, Chemical industry.

Also known as Laboratory Sterilizer, Horizontal Pressure Sterilizer, Laboratory Horizontal Autoclave,.

AUT22-150 HORIZONTAL AUTOCLAVE

High Quality Stainless steel chamber with drying function

Safety features for over temperature and pressure

Equipped with a built in printer

Automatic opening of safety valve if pressure exceeds 0.24MPa

Door remains locked if pressure exceeds 0.027MPa

Over temperature, over pressure, auto protection device

Automatic power cut off and water cut off in case of water shortage



SPECIFICATIONS

Model	AUT22-150
Capacity	150 L
Adjustment of Temperature	40°C-134°C
Sterilization Temperature	134°C
Sterilization Time	0-99 min
Heat Average	±2°C
Working Pressure	0.22 MPa
Time of Drying	0-99 min
Chamber Dimension	480×850 mm
Overall Dimension (LxWxH)	1400x600x1300 mm
Packing Size	800 x 1650 x 1600 mm
Weight	270/360 kg
Power	6000 W
Power Supply	380V, 50Hz



Biozef

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: info@biozef.com | Website: biozef.com