

DRY BATH INCUBATOR BAC11-100



DRY BATH INCUBATOR BAC11-100

Compact design with stable operation, easy cleaning, replacement and disinfection of metal blocks. It is widely used for enzyme reactions, immunoassays, melting and boiling points, incubation and activation of cultures and variation of laboratory procedure. Flexible to accommodate a variety of interchangeable heating blocks.

Used in Clinical, General Chemistry, Preservation, Reactions of sample, DNA amplification, Initial Denaturation of electrophoresis.

Also known as Laboratory Dry Bath.

BAC11-100 DRY BATH INCUBATOR

Microprocessor intelligent control

The unique design, Special plastic on the external edge of wash tank which is anti-corrosion, anti-scald

Stainless steel interior

Built-in frequency scanning function

Water level control

High ultrasound power and low noise



SPECIFICATIONS

Model	BAC11-100
Capacity	6 L
Function	Basic model
Temperature Range	RT+5-100°C
Temperature Stability	$\leq \pm 0.3^{\circ}\text{C}$ at 37°C
Temperature Uniformity	$\leq \pm 0.5^{\circ}\text{C}$
Time Range	1 min-9999 min
Display Accuracy	0.1°C
Cleaning Tank (LxWxH)	300x150x150 mm
Outer Dimension (WxDxH)	420x230x320 mm
Weight	0.8 kg
Fuse Protector	250 V, 1 A / 2 A, $\Phi 5 \times 20$
Maximum Input Power	220
Maximum Output Power	180
Heating Power	NO
Power	150 W
Power Adjustable (%)	NO
Drain	NO
Level Control System	NO
Power Supply	AC 220 / 110 V, 50/60 Hz

OPTIONAL ACCESSORIES

Accessory Code	Name	Description
LS54934	Stands for plates (capacity: 2 pieces)	Stands for plates (capacity: 2 pieces)
LS54946	Stands for gel cards (capacity: 12 x 2)	Stands for gel cards (capacity: 12 x 2)



Biozef

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: info@biozef.com | Website: biozef.com