



DRY BATH INCUBATOR BAC15-150

Compact design with stable operation, easy cleaning, replacement and disinfection of metal blocks. It is widely used for enzyme reactions, immunoassays, melting and boiling points, incubation and activation of cultures and variation of laboratory procedure. Flexible to accommodate a variety of interchangeable heating blocks.

Used in Clinical, General Chemistry, Preservation, Reactions of sample, DNA amplification, Initial Denaturation of electrophoresis.

Also known as Laboratory Dry Bath Chiller.

BAC15-150 DRY BATH INCUBATOR

Microprocessor intelligent control

The unique design, Special plastic on the external edge of wash tank which is anticorrosion, anti-scald

Stainless steel interior

Built-in frequency scanning function

Water level control

High ultrasound power and low noise



SPECIFICATIONS

Model	BAC15-150
Capacity	10 L
Function	Heating function
Temperature Range	RT+5-150°C
Temperature Stability	≤±0.5°C(@40-100°C) ≤±1°C(@>100°V)
Temperature Uniformity	≤±0.3°C(@40°C) ≤±0.5°C(@>100°C)
Time Range	1 min – 99 h 59 min or continuous
Display Accuracy	0.1℃
Cleaning Tank (LxWxH)	300x240x150 mm
Outer Dimension (WxDxH)	420x310x370 mm
Weight	3.3 kg
Fuse Protector	250 V, 3 A /6 A, Φ5x20
Maximum Input Power	900
Maximum Output Power	360
Heating Power	500
Power	400 W
Power Adjustable (%)	30-100
Drain	YES
Level Control System	YES
Power Supply	AC 220 / 110 V, 50/60 Hz

2

OPTIONAL ACCESSORIES

Accessory Code	Name	Description
LS52215	Block	1.5/2.0ml adaptors (6/pack)
LS52228	Block	0.2 mL 24-well Block
LS52241	Block	0.5 mL 12-well Block
LS52254	Block	1.5 mL 6-well Block

Accessory Code	Name	Description
LS52267	Block	2.0 mL 6-well Block
LS52280	Block	15 mL 6-well Block
LS52293	Block	50 mL 3-well Block
LS52306	Block	96-well/Flat Bottom Block



Biozef

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA Email: info@biozef.com | Website: biozef.com