

DRY BATH INCUBATOR BAC19-100



DRY BATH INCUBATOR BAC19-100

Compact design with stable operation, easy cleaning, replacement and disinfection of metal blocks. It is widely used for enzyme reactions, immunoassays, melting and boiling points, incubation and activation of cultures and variation of laboratory procedure. Flexible to accommodate a variety of interchangeable heating blocks.

Used in Pharmaceutical, Chemical, Food Safety, Environment, Quality inspection, Laboratory.

Also known as Laboratory Dual Temperature Dry Bath Incubator.

BAC19-100 DRY BATH INCUBATOR



SPECIFICATIONS

Model	BAC19-100
Capacity	10 L
Function	Basic model
Temperature Range	RT+5-100°C
Maximum Temperature Difference at 40°C	±0.5°C at 100°C
Display Accuracy	±0.1°C
Cleaning Tank (LxWxH)	300x240x150 mm
Outer Dimension (WxDxH)	420x310x370 mm
Weight	2.5 kg
Maximum Input Power	400
Maximum Output Power	360
Heating Power	NO
Power Adjustable (%)	NO
Drain	YES
Level Control System	YES

OPTIONAL ACCESSORIES

Accessory Code	Name	Description
LS52215	Block	1.5/2.0ml adaptors (6/pack)
LS52228	Block	0.2 mL 24-well Block
LS52241	Block	0.5 mL 12-well Block
LS52254	Block	1.5 mL 6-well Block

Accessory Code	Name	Description
LS52267	Block	2.0 mL 6-well Block
LS52280	Block	15 mL 6-well Block
LS52293	Block	50 mL 3-well Block
LS52306	Block	96-well/Flat Bottom Block



Biozef

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: info@biozef.com | Website: biozef.com