

DRY BATH INCUBATOR BAC1E-100



DRY BATH INCUBATOR BAC1E-100

Compact design with stable operation, easy cleaning, replacement and disinfection of metal blocks. It is widely used for enzyme reactions, immunoassays, melting and boiling points, incubation and activation of cultures and variation of laboratory procedure. Flexible to accommodate a variety of interchangeable heating blocks.

Used in Calibration tests, High temperature organic distillation, External circulation, High temperature experiments. Also known as Bath Circulator, Laboratory Bath Circulator.

BAC1E-100 DRY BATH INCUBATOR

Microprocessor temperature controller

Easy maintenance

LCD display with touch key panel for temperature setting

Over temperature alarm system



SPECIFICATIONS

Model	BAC1E-100
Temperature Uniformity	±0.5°C
Outer Dimension (WxDxH)	185x185x90 mm
Weight	1.4 kg
Temperature Precision	±0.5°C
Operation Ambient Temperature	8-30°C
Power Supply	12 V DC, 5A

OPTIONAL ACCESSORIES

Accessory Code	Name	Description
LS54689	Control panel (including board)	
LS54701	Heating tube	



Biozef

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: info@biozef.com | Website: biozef.com