

AIR BATH BAC21-060



AIR BATH BAC21-060

It is widely used in preservation and reactions of samples, DNA amplification, and initial denaturation of electrophoresis and so forth. The LCD display is very easy to setup and use, and it is quite compact.

Used in High temperature organic distillation, External circulation, Calibration tests, High temperature experiments, Laboratory.

Also known as Cooling Bath Circulator, Refrigerated Circulator, Laboratory Refrigerated Bath Circulator.

BAC21-060 AIR BATH



SPECIFICATIONS

Model	BAC21-060
Capacity	4 L
Function	Power adjustable
Temperature Range	RT+5-60°C
Temperature Stability	±0.2°C at 37°C
Temperature Uniformity	≤±0.5°C
Display Accuracy	0.1°C
Cleaning Tank (LxWxH)	300x150x100 mm
Inner Dimension (WxDxH)	215Wx245Dx85H mm
Outer Dimension (WxDxH)	275Wx395Dx150H mm
Weight	8.1 kg
Fan Speed Range	1200-3200 rpm
Fuse Protector	250 V, 2 A / 4 A, Φ5x20
Maximum Input Power	220
Maximum Output Power	180
Heating Power	NO
Power	300 W
Power Adjustable (%)	30-100
Drain	NO
Level Control System	NO
Power Supply	AC 220 / 110 V, 50/60 Hz



Biozef

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: info@biozef.com | Website: biozef.com