

REFRIGERATED MICROCENTRIFUGE CEN46-140R



REFRIGERATED MICROCENTRIFUGE CEN46-140R

This compact, powerful micro centrifuge is useful to separate or sediment small volume samples at high speed. The short-spin key, soft brake, FastTemp features optimizes the overall function of the centrifuges. Faults are diagnosed automatically and displays fault code. These hybrid micro-centrifuge can run PCR tubes, Capillary tubes along with standard tubes.

Used in Molecular Biology Separations, Clinical, Labs, Biochemistry, Tissue Culture, Genomics, Drug discover. Also known as Microfuge, Refrigerated Microcentrifuge, Laboratory Microcentrifuge.

CEN46-140R REFRIGERATED MICROCENTRIFUGE

Microprocessor controller

LCD display

RCF can be set up directly, without RPM to RCF translation

Memory of 9 programs

9 levels of acceleration and 9 levels of deceleration

Servomotor was adopt for lid open & lid lock, emergency lid release.

Aerosol-tight quick lock rotors for safe centrifugation of hazardous samples

Inner chamber material: Stainless Steel

Rotors are in aeronautical aluminum material

Electronic door interlock and Automatic rotor identification and Imbalance protection

Faults are diagnosed automatically, display fault code.

Ergonomic operating and information panel.

CFC-free refrigerants system (TECUMSEH EUROPE COMPRESSOR), with both pre-cooling and standstill cooling function.



SPECIFICATIONS

Model	CEN46-140R
Maximum Capacity (No of tubes x Vol.)	24x1.5/2 ml
Temperature Range	-10°C to 35°C
Temperature Accuracy	± 1°C
Maximum Speed RPM	14000
Speed Accuracy	± 10 rpm
Maximum RCF	18800xg
Timer Range	1~999 min 59S
Temperature Increment	1°C
Acceleration Rate	9
Deceleration Rate	9
Drive System	Direct, induction motor drive
Overall Dimension	285x400x285 mm
Program	9 user-defined
Noise Level	≤ 54 dB(A)
Weight (Net/Gross)	19 kg
Power Supply	AC 200-240V, 50/60Hz or AC 100-130V, 50/60Hz

OPTIONAL ACCESSORIES

Accessory Code	Name	Description	RPM	RCF _{xg}	Capacity
LS54095	Fixed-Angle Rotor	4xPCR strip	14000	18800 _{xg}	
LS54287	Fixed-Angle Rotor	with adapters for 0.2ml and 0.5ml	14000	18800 _{xg}	24x1.5/2.0 ml



Biozef

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: info@biozef.com | Website: biozef.com