WATER CHILLER CHI11-014



WATER CHILLER CHI11-014

Water chiller is a device used to lower the temperature of water. Water chiller use water as a refrigerant instead of toxic chemicals. This makes them safer for people who have contact with them. Water chiller are overall more efficient. Used in Biotechnology, Laser, Analytical, Automotive, Packaging, Injection Molding, Die Cutting, Food, Beverage, Chemical, Machine tool, Semi-conductor.

Also known as Laboratory Water Chiller.

CHI11-014 WATER CHILLER

The well-known product spleen compressor, high-efficiency shell and tube condenser, evaporator combination, super refrigeration, power saving PID microcomputer full-function control, easy to operate, can accurately control the water temperature within 3°C~35°C.

Unique new design stainless steel opening Type thermal insulation water tank, easy to clean and repair, reasonable internal pipeline layout, effectively reducing energy consumption.

Copper pipes are welded with Smick L30345% silver electrode, with high density and long life.

With current overload protection, high and low voltage switch, delay protection, over temperature protection, antifreeze, abnormal indication system.



SPECIFICATIONS

Model	CHI11-014	
Freezing capacity		
kw	14.5 kw	
kcal/h	12470 kcal/h	
btu/h	49474 btu/h	
Compressor		
Output power	3.7 kw	
hp	5 hp	
Weight	2.5 kg	
Refrigerant		
Control mode	Thermal expansion valve	
Туре	R22 (R407C optional)	
Evaporator(Type)	Tube-in-shell	
Condensor(Water Chiller)		
Туре	Tube-in-shell	
Cooling water flow	60	
In/out pipe	1 v 2 inch	
Water tank capacity	60 L	
Pump		
Туре	Stainless steel centrifugal pump	
Power kw	0.37 kw	
Flow rate	88 l/min	
Working pressure	2 bar	

Chilled wateroutlet	1 inch x1
Pipe coupling	
Chilled water inlet	1 inchx1
Water tank drainage port	1/2 inch
Dimension(LXWXH) mm	1080x570x940 mm
Weight	210 kg
Power	3 ph-380 V/50 Hz (220 V/400 V/415 V/440 V 50 Hz/60 Hz)
Temperature	5-35 ℃
Tolerance	± 0.5 °C (± 1 °C at low load)
Safety protections	High and low pressure controller/anti-freezing switch/overload of pump and compressor protection/overheat protection/delayed protection



Biozef

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA Email: info@biozef.com | Website: biozef.com