# STANDARD FREEZE DRYER FDR11-3ST



# STANDARD FREEZE DRYER FDR11-3ST

An ideal fit equipment for laboratory with a market proven design and the most advanced microprocessor control available on benchtop unit. It exceeds customer demand and is cost effective. It has Eco-friendly CFC free refrigeration system and provides higher performance.

Used in Laboratory, Research, Proteins, Organic Tissues, Waste Products, Plant Material, Polymers, Pharmaceuticals, Nutraceuticals, Plant material.

Also known as Benchtop Freeze Dryer, Tabletop Lyophilizer, Laboratory Benchtop Freeze Dryer, Laboratory Tabletop Lyophilizer, Benchtop Lyophilizer, Laboratory Benchtop Lyophilizer, Standard Freeze Dryer.

# FDR11-3ST STANDARD FREEZE DRYER

7 Inch color touch control LCD display

Display run time & vacuum parameter

The cold trap with freezing function eliminates the low temperature refrigerator

Imported compressor, high capability of water-capture, low noise

Mixed refrigerant, green environmental protection

Built-in heat exchanger effectively reduces the temperature of cold trap

Anti-return oil vacuum pump to prevent the pollution of the material

Transparent bell-cap drying room is safe and visual

Optional distribution defrosting function

Optional nitrogen inflating valve



#### **SPECIFICATIONS**

Model	FDR11-3ST
Туре	Standard
Plate Load Capacity	1.5 L
Tray Diameter	200 mm
Condenser Temperature	<50°C
Water Holding Capacity	3 Kg/24 h
Freeze Drying Surface Area	0.12 m <sup>2</sup>
Vacuum Degree	<10 Pa
Vial φ 22	260
Vial φ 16	480
Vial φ 12	920
Interlayer Spacing	70 mm
Overall Dimension (mm)	500x400x370 mm
Power	850 W
Power Supply	220 V 50 HZ /110 V 60 Hz

### **OPTIONAL ACCESSORIES**

Accessory Code	Name	Description
LS52829	Swing-out Rotor – Adapter	4xCorning T-75 cm <sup>2</sup> Canted-Neck Cell Culture Flasks
LS52855	Swing-out Rotor – Adapter	20x50 ml



## **Biozef**

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA Email: info@biozef.com | Website: biozef.com