

# GENERAL PURPOSE INCUBATOR INC84-400



# GENERAL PURPOSE INCUBATOR INC84-400

General Purpose Incubator are designed to accommodate an ample range of laboratory applications and lends a contamination-free environment for cell and tissue cultures. These incubators serve the purpose for most biological analysis, research, general laboratory applications, biochemical studies, bacteriology, and hematological studies. Used in Quality Control, Medicine Processing Industries, Research, Pharmaceuticals, Microbial Culturing. Also known as Lab Incubator, Laboratory General Purpose Incubator.

## INC84-400 GENERAL PURPOSE INCUBATOR

**ALLCOLD Refrigeration Technology:** Auto defrost, multiple security system, long time running, environmental protection, high efficiency and energy saving, Auto-defrost function, Imported DuPont SUVA R134 a environmental refrigerant.

**ALLIGENT Humidification System:** Automatic water intake, automatic water level control, persistent

**ALLFLOW Perfect Air Current Cycling:** Perfect forced convection, maximum number of working room, minimum temperature recovery time after the opening, world famous axial fan, perfect air current design.

**ALLSENS Programmable PID Control:** Adaptive PID controller precisely controls the temperature and humidity, prevent temperature soaring, keep working room temperature stable and uniformity.

Excellent Imported temperature and humidity Sensor.

Efficient isolation Design



## SPECIFICATIONS

Model	INC84-400
Capacity	400 L
Temperature Range	0-65°C
Ambient Temperature	10~30°C
Temperature Fluctuation	±0.5 at 10-40°C
Temperature Uniformity	±1.5
Temperature Resolution	0.1°C
Relative Humidity	Below 70%
Sterilization Function	No
Humidity Range	40-95 %RH
Humidity Fluctuation	±2 RH
Interior	SUS304 Stainless Steel Materials
Heat insulator material	Imported environmental protection material
Timer Range	0-99 hrs, 0-9999 min
Convection Mode	Forced Convection
Internal Dimension (WxDxH)	601x639x1052 mm
Overall Dimension (WxDxH)	745x930x1700 mm
Package Size	815x1090x1907 mm
Shelves/Trays	4
Weight	158.5/188 kg
Power	1350 W
Power Supply	Single phase AC220 V/50 Hz





**Biozef**

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA  
Email: [info@biozef.com](mailto:info@biozef.com) | Website: [biozef.com](http://biozef.com)