

VERTICAL LAMINAR AIR FLOW LAF33-0800



VERTICAL LAMINAR AIR FLOW LAF33-0800

Engineered to create a particle-free working environment and provide product protection. It is suited for use with non-hazardous contaminants and creates a clean work environment over a wide range of applications.

Used in Electronic sectors, Industrial sectors, Medical, Pharmaceutical, Healthcare.

Also known as Tissue Culture Hood, Laminar Air Flow Cabinet, Laboratory Laminar Flow, Laboratory Laminar Air Flow, Laminar Flow Cabinet, Minimal-Turbulence Air Flow, Laminar Flow Cabinet, Laminar Flow Hood, Laminar Flow.

LAF33-0800 VERTICAL LAMINAR AIR FLOW

Microprocessor controller

Pre-filter: Polyester fiber, washable

UV Lamp: Emission of 253.7 nanometers



SPECIFICATIONS

| | |
|---------------------------|---|
| Model | LAF33-0800 |
| Type | Vertical Laminar Flow |
| Average Air Flow Velocity | 0.3~0.5m/s, air speed adjustable |
| HEPA Filter Efficiency | 99.99% efficiency at 0.3 μ m |
| UV Lamp | 20W×1 |
| Fluorescent Lamp | 14W×1 |
| Max Opening | 490 mm |
| Front Window | Manual, 5 mm toughened glass, anti-UV |
| Caster | Universal wheel with leveling feet |
| Chamber Material | Cold-rolled steel coated with anti-bacteria powder coating, Work table: Stainless Steel 304 |
| Standard Accessory | Fluorescent lamp, UV lamp*2, Base stand |
| Work Surface Height | 660 mm |
| Internal Size in (WxDxH) | 800x600x540 mm |
| Overall Dimension | 802x650x1550 mm |
| Packaging Size | 960x800x1800 mm |
| Display | LED |
| Noise Level | < 60dB |
| Weight | 116 kg |
| Power | 350 W |
| Power Supply | AC 220V±10%, 50/60 Hz; 110V±10%, 60HZ |



Biozef

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: info@biozef.com | Website: biozef.com