

# SINGLE-HOLE LAMP OPL5F-60



# SINGLE-HOLE LAMP OPL5F-60

Single-hole lamp is suitable for urology, ENT, gynecology examination and general outpatient surgery partial auxiliary lighting. Easy to move with brakes and more suitable for cutting off power with battery.  
Used in Dental implant surgery, Medical unit, Surgery, Operation theatre.  
Also known as Surgical LED Light, LED operation theatre light, LED OT light.

## OPL5F-60 SINGLE-HOLE LAMP

An imported LED cold light source is adopted  
Digital means are adopted for stepless regulation of LED brightness  
With electric focusing function  
The removable handle sheath can be disinfected at the high temperature of 135°C.  
Imported spring arm  
The imported switch power supply is adopted to control the voltage, making the work voltage permanently stable  
The no welding titanium alloy arm and the streamline-designed lamp cap better meet the design requirements of modern clean laminar flow operation rooms



## SPECIFICATIONS

Model	OPL5F-60
Illumination	160000 $\geq$ Ec $\geq$ 80000 Lux / 160000 $\geq$ Ec $\geq$ 80000 Lux
Diameter of spot	10-28 cm
Depth of light beam	$\geq$ 700 mm
Brightness level adjustment	CPU light-dimmer
The value of the total irradiance	<6mW / m <sup>2</sup> lx
Diameter of lamp holder	700 / 700 mm
Shift of major and stand by lamps	Automatic
Total irradiance	$\leq$ 600W/m <sup>2</sup>
Color rendering Index (Ra)	100 $\geq$ Ra $\geq$ 85
Color Temperature (K)	4500 $\pm$ 500 K
Bulb power W (24V)	150 / 150 W
Power supply	220 $\pm$ 20% 50 Hz
Input power	400+10%
Ceiling height for installation (cm)	2.8-3.2 m



**Biozef**

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: [info@biozef.com](mailto:info@biozef.com) | Website: [biozef.com](http://biozef.com)