

GRADIENT TOUCH SCREEN THERMAL CYCLER PCR13-096



GRADIENT TOUCH SCREEN THERMAL CYCLER

PCR13-096

Engineered by finest quality and leading edge technology according to the advance technology and market norms under the direction of competent experts. Simple, intuitive programming, cost-efficient, fast setup and convenient to use makes it an ideal choice.

Used in Analytical Laboratories, Molecular biology, Gene amplification, Gene Expression, Research, Development, Food Science, Pharmaceutical, Life Science, Animal Diagnostics.

Also known as Gradient PCR Machine, Laboratory Gradient PCR Thermal Cycler, Gradient PCR Thermocycler, Laboratory Gradient PCR Thermocycler.

PCR13-096 GRADIENT TOUCH SCREEN THERMAL CYCLER

The most advanced peltier-based semiconductor technology

Highly performance universal power supply

Large 5.7 inch high-definition LCD display

Graphical user interface in English and Chinese

Power-down data protection

Metal shell, solid, practical, beautiful and generous

Stepless adjustable hot lid

Lid can be positioned at any angle

High-sealing reaction zone, to ensure stable and reliable test



SPECIFICATIONS

Model	PCR13-096
Temperature Range	0°C~99.9°C
Max.Heating Ramp Rate	5°C/s
Max.Cooling Ramp Rate	5°C/s
Block Formats	96x0.2 ml (A) / 54x0.5 ml (B) / 96x0.2 ml+77x0.5 ml (C) / 384well (D)
Display Interface	7' LCD
Heating/Cooling adjustable rate	0.1°C/s~4.0°C/s
Uniformity	≤±0.2°C
Accuracy	≤±0.1°C
Gradient Temp Range	30~99°C
Thermal Gradient Span	1~30°C
Gradient Uniformity	≤0.2°C(single row)
Hot Lid Temperature	20~110°C
Max.No.of Cycle	999
Communication	USB2.0 / RS 232 / RJ45
Temp Control Mode	Block, tube*
Memory Capacity	2000*
Note	*10~100µl Optional **Unlimited with use of USB memory stick

Intelligent Diagnosis	108
Dimension (W×D×H)	380x270x250 mm
Weight	8.1 kg



Biozef

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: info@biozef.com | Website: biozef.com