

REAL-TIME MINI THERMAL CYCLER PCR23-08



REAL-TIME MINI THERMAL CYCLER PCR23-08

Mini-PCR works interchangeably with standard PCR assays, reagents, and consumables. It is portable, user friendly, small in size and easy to program with an intuitive user interface. It is benefit for students to understand with the animation presentation capabilities of the PC operating software.

Used in Incubation, Research, Development, Food Science, Pharmaceutical, Life Science, Animal Diagnostics, Analytical Laboratories, Molecular biology, Gene amplification, Gene Expression.

Also known as Laboratory Mini PCR, Mini PCR Machine, Laboratory Mini PCR Machine.

PCR23-08 REAL-TIME MINI THERMAL CYCLER

Peltier technology: Solid-state, thermoelectric heating and cooling unit for improved control and durability

Bottom detection system provides greater accuracy and sensitivity of measurements

High-powered photomultiplier provides sensitive detection

Long life LED excitation light source does not need maintenance or preheating

Hot-lid feature allows oil-free operation

Advanced PID control ensures the accuracy of temperature control



SPECIFICATIONS

Model	PCR23-08
Temperature Range	4~100°C
Ambient Temperature	Operation Temp: 15-30°C; Storage Temp: 10-60°C
Ambient Humidity	Operation Humidity: 15-90% Relative Humidity; Storage Humidity: 5-95% Relative Humidity
Max. ramp rate	3°C / s
Reaction volume	10-150 µL
Block Formats	8 Wells
Block Material	Peltier
High Resolution Melt	Supported Resolution to 0.5°C
Multiplexing	Detect up to 2 dyes simultaneously, 470 / 520 nm(SYBR / FAM) and 565 / 625 nm(ROX / Texas Red)
Thermal Uniformity	±0.2°C
Thermal Accuracy	±0.2°C
Light Source	High power LED
Detector	Photodiode
PC Operation system	WIN2000
XP	WIN7
WIN8	Dimension (W×D×H)
190x205x98 mm	Weight
2.1 kg	Power Supply

OPTIONAL ACCESSORIES

Accessory Code	Name	Description	Excitation Wavelength(450-590 nm)	Emission Wavelength	Detected Fluorescence
LS52124	Block A	48x0.2 ml (4 channels, auto hot-lid)	Standard Channels: F1:470 nm, F2:523 nm, F3:543 nm, F4:571 nm	Standard Channels: F1:525 nm, F2:564 nm, F3:584 nm, F4:612 nm	F1: FAM, SYBR Green I F2: HEX, VIC F3: TAMRA, JOE, Cy3 F4: TEXAS-RED, ROX
LS52137	Block B	48x0.2 ml (2 channels, manual hot-lid)	F1:470 nm, F2:564 nm	F1: 525 nm, F2: 564 nm	F1: FAM, SYBR Green I F2: HEX, VIC



Biozef

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: info@biozef.com | Website: biozef.com