THERMAL CYCLER PCR41-099



THERMAL CYCLER PCR41-099

Thermal Cyclers have become an essential tool for DNA amplification, and are considered by many as the workhorse of the laboratory. It provides outstanding performance in a compact and user friendly design. Better performance, efficiency and faster optimization makes it a perfect choice for any laboratory.

Used in Research, Development, Food Science, Pharmaceutical, Life Science, Animal Diagnostics, Analytical Laboratories, Cloning, Sequencing, Gene Expression, Gene Amplification..

Also known as DNA Amplifier, Thermocycler, PCR Machine, Laboratory Thermocycler, Laboratory PCR Machine, Laboratory DNA Amplifier..

PCR41-099 THERMAL CYCLER

Adjustable pressure hot lid, to preventvolatilizing and dewing Hot lid with pressure alarm device, toprevent damaging test tube by too much

Convenient and flexible module replacement mode

Innovative module wire socket designachieves module replacement without wire

The unique left-right design for amplication area and operating area makes operator more convenient and safer



SPECIFICATIONS

pressure

Model	PCR41-099		
Temperature Range	0°C~99.9°C		
Max.Heating Ramp Rate	4.0°C/s		
Max.Cooling Ramp Rate	3.5°C/s		
Block Formats	96x0.2 ml (A) / 54x0.5 ml (B) / 96x0.2 ml+77x05 ml (C) / 384well (D)		
Display Interface	5.7′ LCD		
Heating/Cooling adjustable rate	0.1°C/s~4.0°C/s		
Uniformity	≤±0.2°C(20~75°C)		
Accuracy	≤±0.2°C		
Hot Lid Temperature	30~115°C		
Max.No.of Cycle	99		
Communication	USB2.0 / RS 232 / RJ45		
Temp Control Mode	Block, tube		
Memory Capacity	200		
Dimension (W×D×H)	380x270x250 mm		
Weight	7.2 kg		
Power Supply	85∼264 V AC , 47∼63 Hz		

ACCESSORIES

Accessory Code	Name	Description
LS53626	Block A	64×0.2 ml

OPTIONAL ACCESSORIES

Accessory Code	Name	Description
LS53530	Block B	36×0.5 ml



Biozef

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA Email: info@biozef.com | Website: biozef.com