

2°C-10°C MEDICAL REFRIGERATOR REF11-1500



2°C-10°C MEDICAL REFRIGERATOR REF11-1500

Engineered to meet the demanding requirements of laboratory research. Major feature like forced air circulation system makes this product highly effective and reliable to provide quick freezing. Designed Environment friendly with no ozone-damaging chemicals and space saving with easier cleanability.

Used in Industry, Cosmetic, Pharmaceutical, Electronics, Laboratory, Medical, Research.

Also known as Laboratory Medical Refrigerator.

REF11-1500 2°C-10°C MEDICAL REFRIGERATOR

Microprocessor controller, temperature ranging from +2°C to +8°C, can be set freely, controlling precision 1°C, display accuracy 0.1°C. Room temperature ranging from 0°C to 32°C

Combined with two exact sensors and auto defrost

Audible and visual alarm

Upright type, Exterior made from stainless steel, interior made from ABS material. Four units lockable Caster are mounted under the bottom

Two-layer glass door, and inert gas inside. and lockable

Interior fluorescent lighting

Adjustable 12 units shelves made of quality steel wire

Forced air circulation system

One unit of Germany Danfoss compressor and two units of EBM fan motor

Highly effective condenser and expansile evaporator to provide quick freezing

Optional: temperature printer or chart recorder, 7 days inkless graphic temperature recorder



SPECIFICATIONS

Model	REF11-1500
Capacity	1500 L
Temperature Range	2~8°C
Refrigerant	R134a, CFC free
Refrigeration System	International famous compressor and Germany EBM fan motor
Controller	Microprocessor Control with LCD Display
Alarms	High & low temperature alarm, Door open alarm, Sensor failure alarm
External Size	748x1800x1965 mm
Package Size	920x1950x2140 mm
Optional Accessories	Remote alarm system, Chart recorder
Weight	230/260 Kgs
Power	830W
Power Supply	220V,50/ 60HZ, 110V,50/60HZ



Biozef

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: info@biozef.com | Website: biozef.com