

# ORBITAL SHAKER SHA5E-070



# ORBITAL SHAKER SHA5E-070

Allows for easy and accurate rack placement, data retrieval on power failure and slow start up function prevents liquid spillage. Applications like stability and dissolution studies, liquid extractions, protein precipitation studies, small peptide synthesis and dilutions makes it an ideal choice.

Used in Stability, Dissolution Studies, Liquid Extractions, Protein Precipitation, Small Peptide Synthesis, Dilutions.  
Also known as Laboratory Orbital Shaker.

## SHA5E-070 ORBITAL SHAKER

Three-dimensional rocking motion

Max. load capacity is 5kg with platform

Double LCDs for independent display of time and speed

Various platform accessories are available

DC Motor



## SPECIFICATIONS

Model	SHA5E-070
Speed Range	10-70 rpm
Timing Range	1 min-19 h59 min
Motion	Reciprocal
Angle Range	9°
Motor rating Input [W&#93	40
Motor rating output [W&#93	24
Maximum Load Capacity	5 kg
Overall Dimension	360×430×106 mm
Display	LCD
Weight	9 kg
Fuse	250 V,1 A, Φ5x20
Power	50 W
Power Supply	100-240 V, 50/60 Hz

## OPTIONAL ACCESSORIES

Accessory Code	Name	Description
LS52878	Universal attachment, black	
LS52891	Fixing clip for flask volume 25 ml	
LS52904	Fixing clip for flask volume 50 ml	

Accessory Code	Name	Description
LS52954	Fixing clip for flask volume 500 ml	
LS52990	Fixing clip attachment	
LS53038	Dish platform with non-slip mat and fixed string(8 pcs)	

LS52917	Fixing clip for flask volume 100 ml	
LS52942	Fixing clip for flask volume 200 / 250 ml	

LS53050	Universal attachment with 4 bars	
LS53062	Lengthways roller attachment	



**Biozef**

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA  
Email: [info@biozef.com](mailto:info@biozef.com) | Website: [biozef.com](http://biozef.com)