SYNTHESIZING ULTRAPURE WATER SYSTEM WPS67-060FV



SYNTHESIZING ULTRAPURE WATER SYSTEM WPS67-060FV

Ultrapure water system is sub-economic choice for high grade experiments. This level of purification is required for advanced analytical techniques, such as HPLC, and is commonly used for semi-conductor manufacturing. Used in Laboratory, Manufacturing, Reefkeeping, Aquarium, Laboratory, Research.

Also known as Laboratory Ultrapure water system.

WPS67-060FV SYNTHESIZING ULTRAPURE WATER SYSTEM

With tap water inlet, to produce RO water and ultrapure water, quality can reach to 18.2 M Ω .cm.

Built-in 20 liters airtight plastic pressure water tank

Built-in 13 liters high-capacity polishing resin cartridge

Unique design and easy-to-replace cartridges pack unit.

Data storage and RS 232/USB communication port.

3 way on-line water quality sensor, multiple alarm.

Life-span of cartridges' display and alarm.

System circulation function, system sterilization procedure.

Molding process, high-strength, streamline plastic shell.

The graphic display clearly indicates all system's parameters. From water quality to knowing when it is time to change the purification pack,you'll see at a glance what is need

For ease-of-use, the main purification technologies are contained in an innovative all-in-one pack that mean you can change it in just a couple of minutes.

The system requires no special installation, connect the system to your tap water supply it's ready to use.



SPECIFICATIONS

| Model | WPS67-060FV |
|--------------------------|---|
| Feed Water Requirements* | |
| Water Inlet | Tap water |
| Temperature | 5-45°C |
| Pressure | 1.0-4.0 Kgf/cm ² |
| Bacteria | <0.1 cfu/ml |
| DimensionLxWxH | 570x600x1500 mm |
| Weight | 60 kg |
| Power Consumption (W) | 120 W |
| Power Supply | AC110-220 V, 50/60 Hz |
| Note | *The quality of output water accords with the quality of inlet water. |
| Ultrapure Water Quality | |
| Heavy Metal Ion | <0.1 ppb |
| Endotoxin | <0.001 EU/ml |
| Rnases | <0.01 ng/ml |
| Dnases | <4pg/µl |
| Feed Water Requirements | |

| Output | 60 L/hrs at 25°C |
|----------------------------------|------------------|
| Flow rate (with pressure tank) | - |
| Resistivity (25°C) | 18.2 MΩ.cm |
| TOC* | 3 ppb |
| Particle (>0.1µm) | <1/ml |
| Conductivity of RO water quality | < tap waterx4% |



Biozef

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA Email: info@biozef.com | Website: biozef.com