

TOC ANALYZER



TOC ANALYZER

TOC analyzer directly shows the total organic carbon content in water or liquid solutions. It is designed to make testing easier, reproducible and accurate. TOC analyzers maximize both sensitivity and productivity, making them the ideal choice for monitoring in wide range of aqueous samples.

Used in Water for injection, Cleaning validation, Environmental, Chemical, Pharmaceutical Industries, Research, Laboratory.

Also known as Laboratory TOC Analyzer, Total Organic Carbon Analyzer.

ANA51-01DL TOC ANALYZER

Automatic sample introduction with enter of trace sample, we can control the value of the trace sample. No contamination will occur during testing which will be harmful to human being and environment.

It adopts UV Catalytic oxidation during which there is no need to add acid, gas or catalytic with low lost of routine maintenance cost.

7 inches touch screen with operation panel, which is easy to operate and maintain.

The system is set with password for protection which is in compliance with FDA-21 CFR Part11 requirements. Also, it is in compliance with USP32-643 requirements.

Automatic alarm when the value is beyond maximum setting value to protect the instrument and to avoid any incorrect operation.

Auto sampler is optional which can be used for testing various different samples without person.

Special designed for testing water less than 1.5 ppm. Online and office testing function can be easily switched.

8GB mass storage memory which does not restrict date and time.

Less than 3 minutes for each analysis.

Clear historical records which is traceable according to analysis date.

Data for specific whole day can be derived and saved to USB directly.

Equipped with Bluetooth printer which is easy to operate and print quickly.

Modular design ensures quick installation and easy maintenance.

Optional online monitoring device meets different requirements.



SPECIFICATIONS

Model	ANA51-01DL
Detection limit	1 ppb
Max Tolerance	±5%
Analysis Time	3 min
Response Time	within 10 min
Sample Temperature	1-95°C
Sample flow speed	3 ml/min
Relative humidity	≤85%
Drifting	±5%
Repeatability tolerance	≤3%
Working Environment	10-40°C with temperature change ±5°C/d
Dimension	440x220x300 mm
Power	100 W

Power Supply	220/110 V ±10%
Frequency	50 Hz +1 Hz

ANA52-01DL TOC ANALYZER

Automatic sample introduction with enter of trace sample, we can control the value of the trace sample. No contamination will occur during testing which will be harmful to human being and environment.

It adopts UV Catalytic oxidation during which there is no need to add acid, gas or catalytic with low lost of routine maintenance cost.

7 inches touch screen with operation panel, which is easy to operate and maintain.

The system is set with password for protection which is in compliance with FDA-21 CFR Part11 requirements. Also, it is in compliance with USP32-643 requirements.

Automatic alarm when the value is beyond maximum setting value to protect the instrument and to avoid any incorrect operation.

Auto sampler is optional which can be used for testing various different samples without person.

Special designed for testing water less than 1.5 ppm. Online and office testing function can be easily switched.

8GB mass storage memory which does not restrict date and time.

Less than 3 minutes for each analysis.

Clear historical records which is traceable according to analysis date.

Data for specific whole day can be derived and saved to USB directly.

Equipped with Bluetooth printer which is easy to operate and print quickly.

Modular design ensures quick installation and easy maintenance.

Optional online monitoring device meets different requirements.



SPECIFICATIONS

Model	ANA52-01DL
Detector range	0.001-1.500 mg/L (ppm)
Detection limit	1 ppb
Max Tolerance	±5%
Analysis Time	3 min
Response Time	within 10 min
Sample Temperature	1-95°C
Sample flow speed	3 ml/min
Relative humidity	≤85%
Drifiting	±5%
Repeatability tolerance	≤3%
Working Environment	10-40°C with temperature change ±5°C/d
Dimension	440x220x300 mm
Power	100 W
Power Supply	220/110 V ±10%
Frequency	50 Hz +1 Hz

ANA53-50DL TOC ANALYZER

TOC detector with 24 bits data solution extends monitoring range. Controlling system with 32bin processing technology greatly improves performance.

Signal management system of our own patent law which has great advantages of online setting, real-time monitoring, self-testing and flow speed controlling ensure high performance and safe operation.

Weak current system design ensures operation safety.

Compact design for TOC saves bench top space and also makes TOC an ideal choice for laboratory.

Automatic leak check system to avoid operation mistakes and improve instrument performance, so as to ensure operation safety and instrument's safety.

Flow rate controlling system to avoid any effect caused by flow rate fluctuation which ensures accurate data.



SPECIFICATIONS

Model	ANA53-50DL
Detector	NDIR
Detection limit	50 µg/l (ppb)
Parameters	TC, TIC, TOC, NPOC
Method	High Temperature Combustion
Operation	PC Control
Gas Requirement	Oxygen/Nitrogen ≥ 99.995%
Measurement Range	0-30000 mg/l (ppm)
Repeatability	3%
Maximum Salinity	85 g/l
Power	200 W
Power Supply	AC 220 V or AC 110 V
Frequency	50/60 Hz

ANA54-50DL TOC ANALYZER

TOC detector with 24 bits data solution extends monitoring range. Controlling system with 32bin processing technology greatly improves performance.

Signal management system of our own patent law which has great advantages of online setting, real-time monitoring, self-testing and flow speed controlling ensure high performance and safe operation.

Weak current system design ensures operation safety.

Compact design for TOC saves bench top space and also makes TOC an ideal choice for laboratory.

Automatic leak check system to avoid operation mistakes and improve instrument performance, so as to ensure operation safety and instrument's safety.

Flow rate controlling system to avoid any effect caused by flow rate fluctuation which ensures accurate data.



SPECIFICATIONS

Model	ANA54-50DL
Detector	NDIR
Detection limit	50 µg/l (ppb)
Parameters	TC, TIC, TOC, NPOC
Method	Wet Chemical Oxidation by UV
Operation	PC Control
Gas Requirement	Oxygen/Nitrogen ≥ 99.995%
Measurement Range	0-10000 mg/l (ppm)
Repeatability	3%
Maximum Salinity	85 g/l
Power	200 W
Power Supply	AC 220 V or AC 110 V
Frequency	50/60 Hz

ANA55-20P AUTOSAMPLER FOR TOC ANALYZER

Compact design, easy to put on bench top.

Easy to use, no need for special training.

20 positions auto sampling which saves time.

Adopts USB to connect with PC.

Connect with TOC to realize auto-sampling.

Equipped with Multi-sensors for real-time monitoring to ensure instrument safety.

Run for long time with good stability, no need for special maintenance.

Compatible with model AT121 and AT122.



SPECIFICATIONS

Model	ANA55-20P
Sample Position	20
Sample Volume	30/60 ml
Interface	USB
Output	120 W
Power Supply	100~240 V
Frequency	50/60 Hz



Biozef

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: info@biozef.com | Website: biozef.com