PORTABLE AUTOCLAVE



PORTABLE AUTOCLAVE

Portable Autoclave is used for general purpose sterilization. Saturated steam is used to sterilize articles rapidly and efficiently. It is also used as a cooker in plateau areas and also for making high quality drinking water in Drinking Water Plant.

Used in Medical, Research Institutions, Laboratory, Drinking Water Plant, Food industry, Hospital, Agriculture, Hospital, Scientific Research..

Also known as Portable Sterilizer, Steam Autoclave Sterilizer, Portable Autoclave, Pressure Steam Sterilizer, Portable Pressure Steam Sterilizer, Dental Autoclave.

AUT41 PORTABLE AUTOCLAVE



SPECIFICATIONS

Model	AUT41-18	AUT41-24	
Capacity	18 L	24 L	
Function	Electric or I	Electric or LPG heated.	
Sterilization Temperature	120	126°C	
Working Pressure	0.14-0.	0.14-0.16 Mpa	
Maximum Working Pressure	0.165	0.165 Mpa	
Chamber Dimension	280x260 mm	280x390mm	
Overall Dimension (LxWxH)	410x410x430 mm	410x410x550 mm	
Chamber Material	Stainle	Stainless Steel	
Weight	14/16 kg	15/17 kg	
Power	2	2 KW	
Power Supply	220 V,	220 V, 50 Hz	





AUT41-24

AUT42 PORTABLE AUTOCLAVE



SPECIFICATIONS

Model	AUT42-18	AUT42-24	
Capacity	18 L	24 L	
Function	Electric	Electric heated	
Sterilization Temperature	12	126°C	
Steam Exhausting Temperature	≤′	≤1°C	
Working Pressure	0.14-0.	0.14-0.16Mpa	
Maximum Working Pressure	0.165	0.165 Mpa	
Chamber Dimension	280x260 mm	280x390mm	
Overall Dimension (LxWxH)	410×410×520 mm	410×410×630 mm	
Chamber Material	Stainle	Stainless Steel	
Weight	14/16 kg	15/17 kg	
Power	2	2 KW	
Power Supply	220 V	220 V, 50 Hz	





AUT43 PORTABLE AUTOCLAVE



SPECIFICATIONS

Model	AUT43-18	AUT43-24	
Capacity	18 L	24 L	
Function	Electric	Electric heated	
Sterilization Temperature	120	126°C	
Steam Exhausting Temperature	≤1	≤1°C	
Working Pressure	0.14-0.	0.14-0.16Mpa	
Maximum Working Pressure	0.165	0.165 Mpa	
Timer Range	0-99	0-99min	
Chamber Dimension	280×260mm	270×500mm	
Overall Dimension (LxWxH)	440×420×630 mm	440×420×750 mm	
Chamber Material	Stainle	Stainless Steel	
Weight	12/14 kg	14/15 kg	
Power	2 1	2 KW	
Power Supply	220 V,	220 V, 50 Hz	







Biozef