

ORBITAL SHAKER



ORBITAL SHAKER

Allows for easy and accurate rack placement, data retrieval on power failure and slow start up function prevents liquid spillage. Applications like stability and dissolution studies, liquid extractions, protein precipitation studies, small peptide synthesis and dilutions makes it an ideal choice.

Used in Stability, Dissolution Studies, Liquid Extractions, Protein Precipitation, Small Peptide Synthesis, Dilutions.
Also known as Laboratory Orbital Shaker.

SHA55 ORBITAL SHAKER

Compact space-saving design fits easily in incubator and refrigerator

Simultaneous display of speed, timer and operating mode

Brushless DC motor ensures maintenance-free, reliable and quiet operation

Electronic time switching clock controls time or continuous operation mode

RS232 interface enables data logging & computer control

Over speed detection and protection

Accommodate a variety of platforms, non-slip rubber mat, conical flasks and other sample containers



SPECIFICATIONS

Model	SHA55-350S	SHA55-350
Speed Range	100-350 rpm (Linear) 100-800 (orbital)	100-350 rpm (Linear) 100-500 (orbital)
Temperature	4-40°C	
Permissible Ambient Temperature	5-40°C	
Shaking Orbit	4 mm	10 mm
Permissible Relative Humidity	80.00%	
Timing Range	1-1199 min	
Motion	Orbital/Linear	
Motor rating Input [W]	28	
Motor rating output [W]	15	
Maximum Load Capacity	2.5 kg	7.5 kg
Operation	Continuous/Timed	
Overall Dimension	340x300x100 mm	420x370x100 mm
Display	LCD	
Weight	8.1 kg	13.5 kg
Power	30 W	
Power Supply	100-240V, 50/60Hz	

OPTIONAL ACCESSORIES

Accessory Code	Name	Description	Unit	For Models
LS53894	Universal attachment with 3 bars			SHA55-350S
LS53906	Fixing clip attachment			SHA55-350S

LS53918	Lengthways roller attachment			SHA55-350S
LS53930	Dish Attachment with non-slip mat			SHA55-350S
LS53942	Universal attachment Bar, black			SHA55-350S
LS53954	Fixing clip for flask volume 25 ml			All
LS53966	Fixing clip for flask volume 50 ml			All
LS53978	Fixing clip for flask volume 100 ml			All
LS53990	Fixing clip for flask volume 200/250 ml			All
LS54002	Fixing clip for flask volume 500 ml			All
LS54014	Universal attachment with 4 bars			SHA55-350
LS54026	Fixing clip attachment			SHA55-350
LS54038	Lengthways roller attachment			SHA55-350
LS54050	Dish platform with non-slip mat and fixed string		8 pcs	SHA55-350



SHA55-350S



SHA55-350

SHA52 ORBITAL SHAKER

- Microprocessor control with simultaneous display of time and speed
- Compact space-saving design fits easily in incubator and refrigerator
- Brushless DC motor ensures maintenance-free, reliable and quiet operation
- Adjustable speed control provides gentle to vigorous agitation
- Multi-functional shaking system
- Audio alarm signals program completion
- Accommodate a variety of platforms, non-slip rubber mat, conical flasks and other sample containers



SPECIFICATIONS

Model	SHA52-250	SHA52-300
Speed Range	50-250 rpm	50-300 rpm
Temperature	Ambient +5-40°C	
Shaking Orbit	20 mm	10 mm
Timing Range	1 min~99h59 min	
Motion	Orbital	
Maximum Load Capacity	2.5 kg	3 kg
Operation	Continuous/Timed	
Overall Dimension	280x270x110 mm	
Display	LED	

Weight	7.2 kg	
Power	50 W	51 W
Power Supply	AC90~240V, 50/60Hz, 2A	AC100~240V, 50/60Hz, 2A

OPTIONAL ACCESSORIES

Accessory Code	Name	Description
LS52480	Flat Platform	
LS52493	Platform--100ml	
LS52506	Platform--250ml	
LS52519	Universal Platform	
LS52532	Platform with springs	



SHA52-250



SHA52-300

SHA53-250 ORBITAL SHAKER

- Microprocessor control with simultaneous display of time and speed
- Compact space-saving design fits easily in incubator and refrigerator
- Brushless DC motor ensures maintenance-free, reliable and quiet operation
- Adjustable speed control provides gentle to vigorous agitation
- Multi-functional shaking system
- Audio alarm signals program completion
- Accommodate a variety of platforms, non-slip rubber mat, conical flasks and other sample containers



SPECIFICATIONS

Model	SHA53-250
Speed Range	50-250 rpm
Temperature	Ambient +5-40°C
Shaking Orbit	10, 15, 20 mm available (15mm by default)
Timing Range	1 min~99h59 min
Motion	Orbital
Maximum Load Capacity	8 kg
Operation	Continuous/Timed
Platform Dimension	270x240 mm
Overall Dimension	320x350x145 mm

Display	LED
Weight	17.5 kg
Power Supply	AC90~240V, 50/60Hz, 2A

OPTIONAL ACCESSORIES

Accessory Code	Name	Description
LS52545	Flask Clamp	
LS52558	Flask Clamp	
LS52571	Flask Clamp	
LS52584	Flask Clamp	

Accessory Code	Name	Description
LS52597	Platform	
LS52610	Platform	
LS52623	Platform	
LS52636	Platform	

SHA58 ORBITAL SHAKER

Compact space-saving design fits easily in small spaces

Brushless DC motor ensures maintenance-free, reliable and quiet operation

Electronic time switching clock controls time or continuous operation mode

Simultaneous display of speed, timer and operating mode

RS232 interface enables data logging & computer control

Over speed detection and protection

Accommodate a variety of platforms, non-slip rubber mat, conical flasks and other sample containers



SPECIFICATIONS

Model	SHA58-800	SHA58-500
Speed Range	100-800 rpm (orbital) 100-350 rpm (Linear)	100-500 rpm (orbital) 100-350 rpm (Linear)
Permissible Ambient Temperature	5-40°C	
Shaking Orbit	4 mm	10 mm
Permissible Relative Humidity	80.00%	
Timing Range	1-1199 min	
Motion	Orbital/Linear	
Motor rating Input [W]	28	
Motor rating output [W]	15	
Maximum Load Capacity	2.5 kg	7.5 kg
Operation	Continuous/Timed	
Overall Dimension	340x300x100 mm	420x370x100 mm
Display	LCD	
Weight	8.1 kg	13.5 kg
Power	30 W	
Power Supply	110V-240V, 50/60Hz	

OPTIONAL ACCESSORIES

Accessory Code	Name	Description	Unit	For Models
LS53894	Universal attachment with 3 bars			SHA58-800
LS53906	Fixing clip attachment			SHA58-800
LS53918	Lengthways roller attachment			SHA58-800
LS53930	Dish Attachment with non-slip mat			SHA58-800
LS53942	Universal attachment Bar, black			SHA58-800
LS53954	Fixing clip for flask volume 25 ml			All
LS53966	Fixing clip for flask volume 50 ml			All
LS53978	Fixing clip for flask volume 100 ml			All
LS53990	Fixing clip for flask volume 200/250 ml			All
LS54002	Fixing clip for flask volume 500 ml			All
LS54014	Universal attachment with 4 bars			SHA58-500
LS54026	Fixing clip attachment			SHA58-500
LS54038	Lengthways roller attachment			SHA58-500
LS54050	Dish platform with non-slip mat and fixed string		8 pcs	SHA58-500



SHA58-800



SHA58-500

SHA54-300 ORBITAL SHAKER

Easy to operate with one touch knob

DC brushless motor for gentle and powerful motion



SPECIFICATIONS

Model	SHA54-300
Speed Range	50-300 rpm
Speed Increment	1 rpm
Timing Range	1 min ~ 99 h59 min
Maximum Load Capacity	3 kg

Overall Dimension	280×270×110 mm
Weight	6.5 kg
Power	45 W
Power Supply	220 V/120 V

SHA56-200 ORBITAL SHAKER

Max. load capacity is 3kg with platform

Double LEDs for independent display of time and speed

Various platform accessories are available

Brushless DC motor ensures maintenance-free, reliable and quiet operation



SPECIFICATIONS

Model	SHA56-200
Speed Range	40-200 rpm
Permissible Ambient Temperature	5-40°C, 80%RH
Shaking Orbit	20 mm
Timing Range	1 min ~ 99 h59 min
Motor rating Input [W]	16
Motor rating output [W]	10
Maximum Load Capacity	3 kg
Overall Dimension	270×330×110mm
Display	LED
Weight	3.1 kg
Power	30 W
Power Supply	100-240 V, 50/60 Hz

OPTIONAL ACCESSORIES

Accessory Code	Name	Description
LS52865	Universal attachment, black	
LS52891	Fixing clip for flask volume 25 ml	
LS52904	Fixing clip for flask volume 50 ml	
LS52917	Fixing clip for flask volume 100 ml	
LS52942	Fixing clip for flask volume 200 / 250 ml	

Accessory Code	Name	Description
LS52954	Fixing clip for flask volume 500 ml	
LS52978	Fixing clip attachment	
LS53002	Dish Attachment with non-slip mat	
LS53014	Universal attachment with 3 bars	
LS53026	Lengthways roller attachment	

SHA59-200 ORBITAL SHAKER

Double LEDs for independent display of time and speed

Various platform accessories are available

Brushless DC motor ensures maintenance-free, reliable and quiet operation



SPECIFICATIONS

Model	SHA59-200
Speed Range	40-200 rpm
Permissible Ambient Temperature	5-40°C, 80%RH
Timing Range	1 min-19 h59 min
Amplitude	20 mm
Motor rating input [W]	16
Motor rating output [W]	10
Maximum Load Capacity	3 kg
Overall Dimension	270×330×110 mm
Display	LED
Weight	3.1 kg
Power	30 W
Power Supply	100-240 V,50/60 Hz

OPTIONAL ACCESSORIES

Accessory Code	Name	Description
LS52865	Universal attachment, black	
LS52891	Fixing clip for flask volume 25 ml	
LS52904	Fixing clip for flask volume 50 ml	
LS52917	Fixing clip for flask volume 100 ml	
LS52942	Fixing clip for flask volume 200 / 250 ml	

Accessory Code	Name	Description
LS52954	Fixing clip for flask volume 500 ml	
LS52978	Fixing clip attachment	
LS53002	Dish Attachment with non-slip mat	
LS53014	Universal attachment with 3 bars	
LS53026	Lengthways roller attachment	

SHA5B-070 ORBITAL SHAKER

Max. load capacity is 10kg with platform

Double LCDs for independent display of time and speed

Various platform accessories are available

DC Motor



SPECIFICATIONS

Model	SHA5B-070
Speed Range	10-70 rpm
Permissible Ambient Temperature	5-40°C, 80%RH
Timing Range	1 min-19 h59 min
Angle Range	9°
Motor rating input [W]	40
Motor rating output [W]	24
Maximum Load Capacity	10 kg
Overall Dimension	360×410×200 mm
Display	LCD
Weight	9 kg
Power	50 W
Power Supply	100-240 V, 50/60 Hz

OPTIONAL ACCESSORIES

Accessory Code	Name	Description
LS52878	Universal attachment, black	
LS52891	Fixing clip for flask volume 25 ml	
LS52904	Fixing clip for flask volume 50 ml	
LS52917	Fixing clip for flask volume 100 ml	
LS52942	Fixing clip for flask volume 200 / 250 ml	

Accessory Code	Name	Description
LS52954	Fixing clip for flask volume 500 ml	
LS52990	Fixing clip attachment	
LS53038	Dish platform with non-slip mat and fixed string(8 pcs)	
LS53050	Universal attachment with 4 bars	
LS53062	Lengthways roller attachment	

SHA5C-080 ORBITAL SHAKER

Max. load capacity is 3kg with platform
 Double LEDs for independent display of time and speed
 Various platform accessories are available
 DC Motor



SPECIFICATIONS

Model	SHA5C-080
Speed Range	10-80 rpm
Permissible Ambient Temperature	5-40°C, 80%RH
Timing Range	1 min-19 h59 min
Angle Range	7°
Motor rating input [W]	16
Motor rating output [W]	10
Maximum Load Capacity	3 kg
Overall Dimension	270×330×130 mm
Display	LED
Weight	3.2 kg
Power	20 W
Power Supply	100-240 V, 50/60 Hz

OPTIONAL ACCESSORIES

Accessory Code	Name	Description
LS52865	Universal attachment, black	
LS52891	Fixing clip for flask volume 25 ml	
LS52904	Fixing clip for flask volume 50 ml	
LS52917	Fixing clip for flask volume 100 ml	
LS52942	Fixing clip for flask volume 200 / 250 ml	

Accessory Code	Name	Description
LS52954	Fixing clip for flask volume 500 ml	
LS52978	Fixing clip attachment	
LS53002	Dish Attachment with non-slip mat	
LS53014	Universal attachment with 3 bars	
LS53026	Lengthways roller attachment	

SHA5E-070 ORBITAL SHAKER

Three-dimensional rocking motion
 Max. load capacity is 5kg with platform
 Double LCDs for independent display of time and speed
 Various platform accessories are available
 DC Motor



SPECIFICATIONS

Model	SHA5E-070
Speed Range	10-70 rpm
Timing Range	1 min-19 h59 min
Motion	Reciprocal
Angle Range	9°
Motor rating Input [W]	40
Motor rating output [W]	24
Maximum Load Capacity	5 kg
Overall Dimension	360×430×106 mm
Display	LCD
Weight	9 kg
Fuse	250 V,1 A, Φ5x20
Power	50 W
Power Supply	100-240 V, 50/60 Hz

OPTIONAL ACCESSORIES

Accessory Code	Name	Description
LS52878	Universal attachment, black	
LS52891	Fixing clip for flask volume 25 ml	
LS52904	Fixing clip for flask volume 50 ml	
LS52917	Fixing clip for flask volume 100 ml	
LS52942	Fixing clip for flask volume 200 / 250 ml	

Accessory Code	Name	Description
LS52954	Fixing clip for flask volume 500 ml	
LS52990	Fixing clip attachment	
LS53038	Dish platform with non-slip mat and fixed string(8 pcs)	
LS53050	Universal attachment with 4 bars	
LS53062	Lengthways roller attachment	

SHA5F-080 ORBITAL SHAKER

Three-dimensional rocking motion
 Max. load capacity is 3kg with platform
 Double LEDs for independent display of time and speed
 Various platform accessories are available
 DC Motor



SPECIFICATIONS

Model	SHA5F-080
Speed Range	10-80 rpm
Permissible Ambient Temperature	5-40°C, 80%RH
Timing Range	1 min-19 h59 min
Angle Range	7°
Motor rating input [W]	16
Motor rating output [W]	10
Maximum Load Capacity	3 kg
Overall Dimension	270×330×130 mm
Display	LED
Weight	2.7 kg
Power	20 W
Power Supply	100-240 V, 50/60 Hz

OPTIONAL ACCESSORIES

Accessory Code	Name	Description
LS52865	Universal attachment, black	
LS52891	Fixing clip for flask volume 25 ml	
LS52904	Fixing clip for flask volume 50 ml	
LS52917	Fixing clip for flask volume 100 ml	
LS52942	Fixing clip for flask volume 200 / 250 ml	

Accessory Code	Name	Description
LS52954	Fixing clip for flask volume 500 ml	
LS52978	Fixing clip attachment	
LS53002	Dish Attachment with non-slip mat	
LS53014	Universal attachment with 3 bars	
LS53026	Lengthways roller attachment	

SHA5G-080 ORBITAL SHAKER

Three-dimensional rocking motion
 Max. load capacity is 3kg with platform
 Various platform accessories are available
 DC Motor



SPECIFICATIONS

Model	SHA5G-080
Speed Range	0-80 rpm
Permissible Ambient Temperature	5-40°C, 80%RH
Angle Range	7°
Motor rating Input [W]	16
Motor rating output [W]	10
Maximum Load Capacity	3 kg
Overall Dimension	270×330×130 mm
Weight	2.7 kg
Power	20 W
Power Supply	100-240 V,50/60 Hz

OPTIONAL ACCESSORIES

Accessory Code	Name	Description
LS52865	Universal attachment, black	
LS52891	Fixing clip for flask volume 25 ml	
LS52904	Fixing clip for flask volume 50 ml	
LS52917	Fixing clip for flask volume 100 ml	
LS52942	Fixing clip for flask volume 200 / 250 ml	

Accessory Code	Name	Description
LS52954	Fixing clip for flask volume 500 ml	
LS52978	Fixing clip attachment	
LS53002	Dish Attachment with non-slip mat	
LS53014	Universal attachment with 3 bars	
LS53026	Lengthways roller attachment	

SHA51-350 ORBITAL SHAKER

- Microprocessor control with simultaneous display of time and speed
- Brushless DC motor ensures maintenance-free, reliable and quiet operation
- Adjustable speed control provides gentle to vigorous agitation
- Audio alarm signals program completion
- Accommodate a variety of platforms, non-slip rubber mat, conical flasks and other sample containers



SPECIFICATIONS

Model	SHA51-350
Speed Range	50-350 rpm
Temperature	4-45°C
Shaking Orbit	10 mm
Timing Range	1 min~99h59 min
Motion	Orbital
Maximum Load Capacity	2 kg
Operation	Continuous/Timed
Overall Dimension	280x260x90 mm
Display	LED
Weight	7.5 kg
Power	50 W
Power Supply	AC100-230V, 60Hz

OPTIONAL ACCESSORIES

Accessory Code	Name	Description
LS54209	Platform	Flat platform with non-slip rubber mat
LS54221	Platform	Double deck flat platform with non-slip rubber mat
LS54233	Platform	Platform with clamps for flasks 100-150ml
LS54245	Platform	Platform with clamps for flasks 250-300ml

Accessory Code	Name	Description
LS54257	Platform	Universal platform with adjustable bars
LS54269	Platform	Universal platform with springs
LS54281	Platform	Sticky pad (not platform, can be put in the platform BX-103551 or BX-103552)

SHA51-300 ORBITAL SHAKER

- Microprocessor control with simultaneous display of time and speed
- Brushless DC motor ensures maintenance-free, reliable and quiet operation
- Adjustable speed control provides gentle to vigorous agitation
- Audio alarm signals program completion
- Accommodate a variety of platforms, non-slip rubber mat, conical flasks and other sample containers



SPECIFICATIONS

Model	SHA51-300
Speed Range	50-300 rpm
Temperature	4-45°C
Shaking Orbit	20 mm
Timing Range	1 min~99h59 min
Motion	Orbital
Maximum Load Capacity	2 kg
Operation	Continuous/Timed
Overall Dimension	280x260x90 mm
Display	LED
Weight	7.5 kg
Power	50 W
Power Supply	AC100-230V, 60Hz

OPTIONAL ACCESSORIES

Accessory Code	Name	Description
LS54209	Platform	Flat platform with non-slip rubber mat
LS54221	Platform	Double deck flat platform with non-slip rubber mat
LS54233	Platform	Platform with clamps for flasks 100-150ml
LS54245	Platform	Platform with clamps for flasks 250-300ml

Accessory Code	Name	Description
LS54257	Platform	Universal platform with adjustable bars
LS54269	Platform	Universal platform with springs
LS54281	Platform	Sticky pad (not platform, can be put in the platform BX-103551 or BX-103552)

SHA51-250 ORBITAL SHAKER

Microprocessor control with simultaneous display of time and speed

Brushless DC motor ensures maintenance-free, reliable and quiet operation

Adjustable speed control provides gentle to vigorous agitation

Audio alarm signals program completion

Accommodate a variety of platforms, non-slip rubber mat, conical flasks and other sample containers



SPECIFICATIONS

Model	SHA51-250
Speed Range	50-250 rpm
Temperature	4-45°C
Shaking Orbit	30 mm
Timing Range	1 min~99h59 min
Motion	Orbital
Maximum Load Capacity	2 kg
Operation	Continuous/Timed
Overall Dimension	280x260x90 mm
Display	LED
Weight	7.5 kg
Power	50 W
Power Supply	AC100-230V, 60Hz

OPTIONAL ACCESSORIES

Accessory Code	Name	Description
LS54209	Platform	Flat platform with non-slip rubber mat
LS54221	Platform	Double deck flat platform with non-slip rubber mat
LS54233	Platform	Platform with clamps for flasks 100-150ml
LS54245	Platform	Platform with clamps for flasks 250-300ml

Accessory Code	Name	Description
LS54257	Platform	Universal platform with adjustable bars
LS54269	Platform	Universal platform with springs
LS54281	Platform	Sticky pad (not platform, can be put in the platform BX-103551 or BX-103552)



Biozef

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: info@biozef.com | Website: biozef.com